

HYTSU[®] T&U[®]

Internal - combustion Counterbalance

Heavy Forklift Truck

V200 SERIES

1 0~2 5 ton V200 Series



CE

Safe / Smart / Strong

Comfortable / Durable

Easy maintain



STANDARD SPECIFICATION

		HYTSU GROUP												
Characteristics	1	Manufacture												
	2	Model		CPCD115	CPCD120	CPCD135	CPCD150B	CPCD140	CPCD160	CPCD180	CPCD200	CPCD250		
	3	Rate Capacity		kg/lb.	11500/25330	12000/26430	13500/29735	15000/33040	14000/30840	16000/35240	18000/39650	20000/44050	25000/55065	
	4	Load Center		mm/inch	600/23.6	600/23.6	600/23.6	600/23.6	1250/49.2	1250/49.2	1250/49.2	1250/49.2	1250/49.2	
	5	Power Type			Diesel	Diesel	Diesel	Diesel	Diesel	Diesel	Diesel	Diesel	Diesel	
Dimension	6	Lifting Height		mm/inch	3000/118.1	3000/118.1	3000/118.1	3000/118.1	3000/118.1	3000/118.1	3000/118.1	3000/118.1	3000/118.1	
	7	Free Lift Height		mm/inch	150/5.9	150/5.9	150/5.9	150/5.9	150/5.9	150/5.9	150/5.9	150/5.9	150/5.9	
	8	Fork Size	L	mm/inch	1220/48	1220/48	1220/48	1220/48	1220/48	1220/48	1220/48	1220/48	1220/48	
	9	Fork Speed (outside)	Min/Max	mm/inch	300/1700			300/1700			300/1700		300/1700	
	10	Mast tilt angle	K/T		6/12	6/12	6/12	6/12	6/12	6/12	3/10	3/10	3/10	
	11	Fork overhang		mm/inch	720/28.3	720/28.3	720/28.3	720/28.3	750/29.5	750/29.5	750/29.5	750/29.5	750/29.5	
	12	Overall dimensions	Length to face of fork	mm/inch	4570/179.9	4570/179.9	4890/191.3	4890/191.3	6680/263	6680/263	7480/294.5	7480/294.5	8280/326	
	13		Overall width	mm/inch	2438/96	2438/97	2438/98	2438/99	2530/99.6	2530/99.6	3025/119.1	3025/119.1	3325/130.9	
	14		Overhead guard height	mm/inch	3150/124	3150/124	3350/131.9	3350/131.9	3800/149.6	3800/149.6	3800/149.6	4000/157.5	4300/169.3	
	15	Turning radins		mm/inch	4350/171.3	4350/171.3	4650/183.1	4650/183.1	5100/200.8	5100/200.8	5600/220.5	5600/220.5	5900/232.3	
Performance	16	Empty load/ Capacity load	travel	km/h	28	28	28	25	30	30	28	28	25	
	17		lifting	mm/s	300	300	230	230	200	200	200	200	200	
	18	Max. gradeability		%	20	20	20	20	20	20	20	20	20	
	19	Self weight		kg/lb.	15500/34140	15500/34140	17400/38325	19000/41850	23000/50660	25000/55065	26000/57270	30000/66080	35000/77090	
Wheel&Tires	20	Tyres	Front	11.0-20-18PR				12.0-24-18PR			14.0-24-18PR	14.0-24-24PR	14.0-24-32PR	
	21		Rear	11.0-20-18PR				12.0-24-18PR			12.0-24-18PR	14.0-24-24PR	14.0-24-32PR	
	22	Tread	Font	mm/inch	1695/66.7				1850/72.9			2200/86.6		
	23		Rear	mm/inch	1795/70.7				2000/78.7			2400/94.5		
	24	Wheelbase		mm/inch	3000/118.1	3000/118.1	3300/130	3300/130	3800/149.6	3800/149.6	3800/149.6	4200/165.4	4200/165.4	
25	Ground clearance		mm/inch	150/5.9	150/5.9	150/5.9	150/5.9	150/5.9	150/5.9	150/5.9	150/5.9	150/5.9		
Drive&Control	26	Engine	Model	6102BZGI				WD615.67G II			WD615.67G3			
	27		Manufacture	PERKINS				STEYR						
	28		Rated output	kw/rpxn	95/2200				95/2200			95/2200		
	29	Transmissions	Type	Hydraulic										
	30		Lever	FWD/RVS	2/2	2/2	2/2	2/2	2/2	2/2	2/2	2/2	2/2	

Note: some latest specifications maybe modified by HYTSU without informing

Tel: 0086 21 5869 0003

Fax: 0086 21 5869 2793

Website: www.hytsu.com

E-mail: info@hytsu.com