

STEEL RIM / POLYURETHANE WHEEL / SOLID TYRE



- I: Divided Steel Rim
- II: Polyurethane Wheel
- III: Press-on Solid Tyre
- IV: Non-marking Solid Tyre
- V: Solid Cushion Tyre



SKIDSTEER TYRE


K 192

CL 718

CL 719

CL 720

	Size	PR	Type	Tread Depth (mm)	Standard Rim(mm)	Dimensions		Max Load 40km/h	Press (kpa)
						Section Width	Overall Diameter		
K192	10-16.5NHS	8	TL	16.5	8.25	245-285	765-800	1880	420
	12-16.5NHS	10	TL	18	9.75	280-325	820-860	2450	420
	12-16.5NHS	12	TL	18	9.75	280-325	820-860	2700	515
CL718	10-16.5NHS	8	TL	15	8.25	245-285	765-800	1880	420
	12-16.5NHS	10	TL	18	8.25	280-325	820-860	2450	420
CL719	10-16.5NHS	8	TL	16	8.25	245-285	765-800	1880	420
	12-16.5NHS	10	TL	18	9.75	280-325	820-860	2450	420
CL720	10-16.5NHS	12	TL	25	8.25	245-285	765-800	2280	555

SOLID TIRE MODEL

Pneumatic Shaped Solid Tire		Press-on Solid Tire	
400-8/3.00D, 3.75	480-8/3.75	9x5x5	10-1/2x5x5
500-8/3.00D, 3.50D	600-9/4.00E	10x4x6-1/2	10-1/2x5x6-1/2
650-10/5.00F	650-16	10x4x6-1/4	10-1/2x6x5
700-12/5.00S	800-16	10x5x6-1/2	10-1/2x6x6-1/2
700-15/5.50S	825-15/6.50T	10x5x6-1/4	12x4-1/2x8
750-15	900-20/7.00	10x6x6-1/2	12x5x8
1000-20/7.50,8.00	16x6-8/4.33R	10x6x6-1/4	12x6-1/2x8
1100-20/8.00	18x7-8/4.33R	13x4-1/2x8	15x5x11-1/4
1200-20/8.00,8.50	21x8-9/6.00E	13-1/2x5-1/2x8	15x6x11-1/4
1400-24/10.00	23x9-10/6.50F	14x4-1/2x8	15x8x11-1/4
15x4-1/2x8/3.00D	23x10-12/8.00G	15-1/2x5x10	15-1/2x6x10
27x10-12/8.00G	250-15/7.00	16x5x10-1/2	16-1/4x5x11-1/4
28x9-15/7.00 (815-15)	300-15/8.00	16x6x10-1/2	16-1/4x6x11-1/4
200/50-10/6.50	355/65-15/9.75	16x7x10-1/2	16-1/4x7x11-1/4
Steel Divided Forklifts Rims		17x5x12-1/8	18x7x12-1/8
500-8	650-10	18x5x12-1/8	18x8x12-1/8
600-9	700-9	18x6x12-1/8	18x9x12-1/8
700-12	825-12 (press on)	20x8x16	21x8x15
28x9-15 (press on)	825-15 (press on)	21x7x15	21x9x15
900-16 (press on)	900-20 (press on)	22x6x17-3/4	22x12x16
No-marking tires available on request		22x8x16	28x10x22
		22x9x16	28x12x22